

# TECHNICAL DATA SHEET W 405 GLITTER PASTE



### **TARGET**

Having shinny, elastic and soft touch of glitter printing.

### **PROPERTY**

It is water based. During the use, does not dry and block the screen. The washing fastness is high. Suitable to ecological standarts.

### **SAFETY**

It is ecological, does not contain harmful chemicals. Should be avoided from eye contact and ingestion. Please kindly see product safety data sheet for detailed information.

### **STORAGE**

Keep containers dry and tightly closed. Store in ventilated place between (5 - 35) °C - (41 - 95) °F of temperature.

Recommended shelf life is 12 months after the production.

#### PACKING

30 Kg

The information on this form is based on our best experience and knowledge. It would not be counted as warranty or quality specification. If requested, our technical staff is at your service.

## APPLICATION

*Fabric* : All type of fabric.

**Printing** : Mix with glitter powder for use. Can be mixed with any type of glitter powder.

Mesh	: ( 12 - 27 ) cm - ( 30 - 70 ) Inch
------	-------------------------------------

*Squeegee* : 55 - 65 Shore and U type.

**Curing** : (150 - 160) °C - (302 - 320) °F 1,5 - 2 minutes.

*Mixture* : To be added % 10-25 Glitter Powder. To reduce the viscosity % 1-3 W 401 can be added but do not use the water. Stir well before use.

*Clean up* : The screen should be cleaned with water.

POLYMATH KİMYA San. ve Tic.Ltd.Şti. +90 212 858 08 89 www.polymathkimya.com